



Top quality hand valves for use with spray nozzles, extensions and handles to suit your application needs. Hand valve assemblies may be made from parts shown on this page. The “typical assembly” shown at right includes 4727 handle, 4688 valve, 4673-8 curved extension with swivel body, TeeJet cap and flat spray tip.



Typical Shutoff Valve Assembly

AA31 for pressures up to 500 PSI (35 bar)

Comfortable palm fitting gun. For use with any TeeJet spray tip. ¼" NPS (M) inlet connection.

Forged brass body and nickel-plated steel trigger. Teflon® valve seat and packing, stainless steel valve stem. Weight 12 oz. (0.34 kg). Also supplied as 31-1/4F with ¼" NPT (F) inlet connection.



AA31

Valves



4688

6466

4688 Trigger Valve with trigger lock. Max. flow rate 2 GPM (7.6 l/min), max. pressure of 250 PSI (17 bar). ¼" NPT (F) inlet connection, 1½"-16 (M) outlet connection. Use with TeeJet and ConeJet® tips, adjustable ConeJet tips or MulteeJet® tips. Brass material.

6466 Trigger Valve, same as 4688, less trigger lock, with extra long trigger. Brass material.




6104

6590

6104 Trigger Valve with trigger lock. Same as 4688 except with ¼" NPT (F) inlet and outlet connections. Brass material.

6590 Trigger Valve, same as 6104, less trigger lock, with extra long trigger. Brass material.



13212
Garden Hose Adapter for 36 Valve

13212 Adapter, ⅜" NPT (F) outlet, ¾" garden hose thread inlet for use with ⅜" 36 valve. Brass material.

Valve Handles

Choice of valve handles — for above valves



4727



4754



4725

Outlet connections are ¼" NPT (M) to fit ¼" NPT (F) inlets of all valves shown. Choice of types for every need.

(B)4727 Sure Grip Handle, brass, rubber-covered, ¼" NPS (M) or BSPT hose inlet connection.

4754 Sure Grip Handle, brass, rubber-covered, ¾" garden hose thread (F) inlet connection.

4725 Handle, made of ½" brass pipe with bushing. Slip hose over pipe to form handle.

Extensions for Valves and Spray Guns



9527

High-Pressure Curved Extensions

9527—for pressures to 1,000 PSI (70 bar). Fits models 23H and 31 GunJet spray guns.

For Pressures up to 1,000 PSI

EXTENSION TYPE AND NUMBER	EXTENSION LENGTH IN INCHES (millimeters)
9527-8	8" (203 mm)
9527-18	18" (457 mm)
9527-24	24" (610 mm)
9527-36	36" (914 mm)
9527-48	48" (1,219 mm)



4673

7715

Straight and Curved Extensions

4673 and 6671—for pressures to 125 PSI (9 bar). 7715—for pressures to 250 PSI (17 bar). Fits models 23L and 31 GunJet® spray guns and trigger valves.



22665-PP

TriggerJet® Extension

22665-PP is for use with 22650-PP TriggerJet spray gun. Maximum pressure rating of 150 PSI (10 bar). Includes straight and 45° adapters. Available in 15" and 24" (38 and 61 cm) lengths.

STRAIGHT WITH FIXED BODY	CURVED WITH SWIVEL BODY	CURVED WITH FIXED BODY	EXTENSION LENGTH
7715-8	4673-8	6671-8	8" (203 mm)
7715-18	4673-18	6671-18	18" (457 mm)
7715-24	4673-24	6671-24	24" (610 mm)
7715-30	4673-30	6671-30	30" (762 mm)
7715-36	4673-36	6671-36	36" (914 mm)
7715-48	4673-48	6671-48	48" (1,219 mm)