



## Type 24216A-NYB

- Can be mounted to 20 mm, 1/2", 3/4" or 1" pipe or equivalent size tubing.
- Provides three spray positions for easy change of spray tips.
- Shutoff position provided between each spray position.
- Features ChemSaver® drip-free shutoff. Requires 10 PSI (0.7 bar) at the nozzle to open check valve.
- Standard diaphragm of EPDM with optional Viton® available.

- Maximum operating pressure of 150 PSI (10 bar).
- 1/2" and 3/4" sizes include mounting hole in upper clamp subassembly for attachment to flat surfaces.
- Mounts to a 3/8" (9.5 mm) hole drilled in pipe or tubing.

PART NUMBER	TO CLAMP ON
24216A-20mm-NYB	20 mm Tubing
24216A-1/2-NYB	1/2" Pipe
24216A-3/4-NYB	3/4" Pipe
24216A-1-NYB	1" Pipe



## Type QJ22187-NYB

- Can be mounted to 1/2", 3/4" or 1" pipe or equivalent size tubing.
- 1/2" and 3/4" sizes include a mounting hole in clamp subassembly for mounting to flat surfaces.
- Allows side mounting to flat surface for protection of nozzle body.
- Features ChemSaver drip-free shutoff. Requires 10 PSI (0.7 bar) at the nozzle to open check valve.
- Standard diaphragm of EPDM with optional Viton available.

- Mounts to a 3/8" (9.5 mm) hole drilled in pipe or tubing.
- Maximum operating pressure of 300 PSI (20 bar).

PART NUMBER	TO CLAMP ON
QJ22187-1/2-NYB	1/2" Pipe
QJ22187-3/4-NYB	3/4" Pipe
QJ22187-1-NYB	1" Pipe



## Type QJ17560A-NYB

- Can be mounted to 20 mm, 25 mm, 1/2", 3/4" or 1" pipe or equivalent size tubing.
- Features ChemSaver drip-free shutoff. Requires 10 PSI (0.7 bar) at the nozzle to open check valve.
- Standard diaphragm of EPDM with optional Viton available.
- Mounts to a 3/8" (9.5 mm) hole drilled in pipe or tubing.
- Maximum operating pressure of 300 PSI (20 bar).

- 1/2" and 3/4" sizes include a mounting hole in upper clamp subassembly for mounting to flat surfaces.

PART NUMBER	TO CLAMP ON
QJ17560A-20mm-NYB	20 mm Tubing
QJ17560A-25mm-NYB	25 mm Tubing
QJ17560A-1/2-NYB	1/2" Pipe
QJ17560A-3/4-NYB	3/4" Pipe
QJ17560A-1-NYB	1" Pipe



## Type QJ7421-NYB

- Can be mounted to 1/2", 3/4" or 1" pipe or equivalent size tubing.
- Mounts to a 3/8" (9.5 mm) hole drilled in pipe or tubing.
- Maximum operating pressure of 300 PSI (20 bar).

- 1/2" and 3/4" sizes include a mounting hole in upper clamp subassembly for mounting to flat surfaces.

PART NUMBER	TO CLAMP ON
QJ7421-1/2-NYB	1/2" Pipe
QJ7421-3/4-NYB	3/4" Pipe
QJ7421-1-NYB	1" Pipe