



QJ350 Compact Nozzle Body for Wet Booms

- Compact design means easier mounting and less interference with boom structure.
- Available with 3 or 5 spray positions for easy change of spray tips or quick boom flushing.
- Shutoff between each spray position.
- Positive indexing keeps the nozzle you select firmly in place.
- Automatic spray alignment using flat fan spray tips.
- Maximum operating pressure of 300 PSI (20 bar).
- Available to fit 20 mm tubing, 1/2", 3/4" and 1" pipe.
- Includes ChemSaver® diaphragm check valve for drip-free shutoff. Standard diaphragm opens at 10 PSI (0.7 bar). See page 65 for additional 21950 ChemSaver spring capacities.
- 1.80 GPM (6.80 l/min) with 5 PSI (0.34 bar) pressure drop.
- Molded hex socket in upper clamp for attaching to flat surfaces.
- Hinged upper clamp reduces assembly time and fits inside common boom channels.



QJ353



QJ355

PART NUMBER	NUMBER OF SPRAY OUTLETS	TO CLAMP ON
QJ353-20mm-NYB	3	20 mm Tubing
QJ353-1/2-NYB	3	1/2" Pipe
QJ353-3/4-NYB	3	3/4" Pipe
QJ353-1-NYB	3	1" Pipe

PART NUMBER	NUMBER OF SPRAY OUTLETS	TO CLAMP ON
QJ355-20mm-NYB	5	20 mm Tubing
QJ355-1/2-NYB	5	1/2" Pipe
QJ355-3/4-NYB	5	3/4" Pipe
QJ355-1-NYB	5	1" Pipe

QC360 Quick TeeJet® Nozzle Body with CAM-LOC Adapter

- Same features as QJ360C multiple nozzle bodies.
- Body designed to fit into standard CAM-LOC style quick couplers allowing for quick change to smaller capacity spray tips.
- Locating nib keeps body properly oriented in CAM-LOC fitting.

PART NUMBER	NUMBER OF SPRAY OUTLETS
QC363-NYB	3
QC364-NYB	4
QC365-NYB	5



QC363



QC364



QC365